

Certificate of Compliance H2F Treated MASONRY TOP PLATE

This is to certify that the following products are in compliance with **AS 1720.1 Timber Structures – Design Methods**, the supplements of **AS 1684.2 – 2010 Residential Timber Framed Construction**, and **AS 1604.1 Specification for preservative treatment, Part:1 Sawn and round timbre** and as described in **NCC2016**.

Product	Description
MASONRY TOP PLATE 90x35	Top Plates for Masonry Walls under Tile and Sheet Roofs

The above products are engineer designed, tested, and certified to the following standards:

- AS 1720.1 “*Timber Structures, Part 1: Design methods*”
- AS/NZS 1170 “*Structural Design Actions*”
- AS 4055 “*Wind Load for Housing*”.

Product details:

Use	<ul style="list-style-type: none"> - (Envelope treated) Top Wall Plates in non-cyclonic areas south of the Tropic of Capricorn as specified in AS1720.1, AS 1684.2 and its supplements, and AS 1604.1. - Refer to Wespine’s Technical Updates 11.2 and 12.2 “TOP PLATES for MASONRY WALLS”, and Wespine’s SDS “H2F Treated Plantation Pine” published on Wespine’s website.
Wind classification/Loading	<ul style="list-style-type: none"> - N1 to N4 In accordance with AS 4055.
Exposure conditions	<ul style="list-style-type: none"> - Must be protected from wetting as per AS 1720.1, and AS 1604.1.
Installation, loads, spans and fastening requirements	<ul style="list-style-type: none"> - In accordance with AS 1720.1. - Spans as per Wespine’s Technincal Updates 11.2 and 12.2 - Fastening requirements as per AS 1684.2.
Requirements for maintaining compliance with NCC	<ul style="list-style-type: none"> - Comply with loads/spans, hazard and wind classes as specified in AS 1720.1, AS 1684.2, AS 1604.1 as well as AS 4055.

This certificate is applicable for all H2F (Blue) treated MASONRY TOP PLATES manufactured by Wespine Industries Pty Ltd.

Sincerely,



Rami Fares
BEng (Civil), MIEAust
Product & Process Engineer